
In the day-to-day life it is the small things that matter. Practical accessories are the necessary supplement to the perfect design of an optimal workplace. Everything must have its place, instructions or information must be clean and visible. Additional devices that avoid stress and provide an overview in the workplace help to noticeably increase efficiency while reducing the workload of employees.


SYSTEM WORKSTATION COMPONENTS



For overview and order in the workplace

With the MiniTec assortment of tool holder plates, tool carriers and various tool holders, you can create an overview and order at your workplace. With this program, the operator has the right holder for every tool.

Tool holder plates



Steel, powder coated, grey, RAL 7035

Is simply attached to the portal structure

Square perforation 10 x 10mm in grid 38mm

ESD capability

Tool carrier with double-joint swivel arm

 Tool carrier

 With double joint swivel arm

 Part no.
 32.0510/0

 ESD tool carrier

 with double joint swivel arm

 Part no.
 32.0510/0

- Steel, painted light grey, RAL 7035
- Capacity 150 N

- Is simply attached to the portal structure
- Square perforation 10 x 10mm in grid 38mm


The aluminum-colored tool holders have a shock- and scratch-resistant plastic coating and a 1.5mm thick, embossed base plate. The holders are matched to the tool holder plates and the tool carrier. All products are also available in ESD version on request.


| All products are also available in ESD vers | sion on request. | | | |
|---|------------------|--|--------------|--|
| | 25 | Tool holder with angled hook end | | |
| | * | Hook Ø 6,3 mm L= 50mm Part No | o. 32.0527/0 | |
| | 1 Alan | L=100mm Part No | o. 32.0651/0 | |
| | 55 | Double tool holder with inclined hook end | | |
| | | Hook Ø 6,3 mm | | |
| | | L= 50mm Part No | . 32.0653/0 | |
| | | L= 75mm Part No | . 32.0654/0 | |
| | 7 | Tool holder with vertical hook end | | |
| | | Hook Ø 6,3 mm | | |
| | 75 | L= 75mm Part No | o. 32.0652/0 | |
| | 55 | Double tool holder with vertical hook end | | |
| | | Hook Ø 6,3 mm | | |
| | | L= 35mm Part No | 32.0508/0 | |
| | 35 49 | L= 50mm Part No | 9. 32.0655/0 | |
| | | L= 75mm Part No | . 32.0656/0 | |
| | 55 | Tool holder for self-service packaging |) | |
| | | Hanger Ø 3,7 mm | | |
| | | L= 125mm, W= 30mm Part No | o. 32.0658/0 | |
| L | 1 | | | |

| 25 m 27 27 27 | Tool clamp simple, small base plate For clamping tools with Ø 7-10 mm Part No. 32.0529/0 |
|------------------------|--|
| | Tool clamp simple, large base plate For clamping tools with Ø 20-25 mm Part No. 32.0528/0 |
| | Double tool clamp For clamping tools withØ 7-10 mm Part No. 32.0506/0 |
| 55 | Magnetic holder Holding force approx. 5 kg Part No. 32.0515/0 |
| S E E E E | Machine holder For tools up to Ø 60 mm Part No. 32.0657/0 |


| | 55 | Chuck holder For tools with a cross section of up to 54 x 19 mm Part No. 32.0531/0 |
|--------|---|---|
| | 55 100 53 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 | Pipe holder, also for hoses, cables etc. For hoses and cables up to 100 mm in diameter Part No. 32.0564/0 |
| | | Screwdriver holder for 6 parts 3 receiving slots 6.5 mm wide and 23 mm deep 3 receiving slots 12.5 mm wide and 23 mm deep Part No. 32.0649/0 |
| ····· | 55 100000000000000000000000000000000000 | Drill / hex socket holder, for 14 parts Mounting holes 2 x Ø 3,2 mm 2 x Ø 4,7 mm 2 x Ø 6,7 mm 2 x Ø 7,7 mm 2 x Ø 8,7 mm 1 x Ø 10,7 mm 1 x Ø 12,7 mm 2 x Ø 16,7 mm |
| 222222 | 55 | Bit holder for 7 bits Mounting holes 7x Ø 7,2 mm Part No. 32.0503/0 |

| 60000000000000000000000000000000000000 | 266 555 6 390 390 | Nut holder for 12 nuts Mounting holes 9 x Ø 24,7 mm 1 x Ø 27,3 mm 1 x Ø 31,7 mm 1 x Ø 34,7 mm |
|--|--|---|
| | ST. TO THE ST. | Wrench holder vertical for 10 keys Receiving slots 1 x 7,5 x 30 mm 2 x 6,5 x 23 mm 2 x 5,5 x 20 mm 2 x 4,5 x 15 mm 3 x 4,0 x 10 mm |
| The second | 55 m h h h h h h h h h h h h h h h h h h | Wrench holder horizontally for 8 keys 8 receiving slots 6.5 x 15 mm Part No. 32.0523/0 |
| | 55 | View storage boxes for 1 box size 7 and 8 Max. material thickness for hanging 4 mm B= 55mm Part No. 32.0509/0 |
| 0 | 10.5 380 55 550 550 | View storage boxes for 5 boxes up to size 8 L= 550mm, H= 38mm Part No. 32.0532/0 |






MAGNET 6 X 14 X 50




TECHN. DATA / ITEMS SUPPLIED

- NeFeB N35, nickel-plated
- Without fastening kit
- Attention: Electric- and memory devices can be faulted by the magnet
- Power density, BHmx = 263kJ/m³
- Remanence, Br = 1170 mT
- coercive field strength Hcj = 955 kA/m
- max. service temperature +80 °C
- Weight = 0.030 kg/piece



APPLICATIONS


- Adhesive magnet for tools
- Use under conveyor belts as tracking, for magnetizable conveying products or at higher conveying speeds
- Fitting for all profiles of profile series 45



ASSEMBLY

- Snap or slip the cover profile into profile groove
- Insert magnet into t-slot
- For fastening: (mighty recommended) Use end cap AL, set screw with square nut or t-slot bar

MAGNET 6 X 9 X 50 MM





Part no. 21.0040/0

- NeFeB N45, nickel-plated
- Without fastening kit
- Attention: Electric- and memory devices can be faulted by the magnet

TECHN. DATA / ITEMS SUPPLIED

- Power density, BHmx = 342kJ/m³
- Remanence, Br = 1320 mT
- coercive field strength Hcj = 955 kA/m
- max. service temperature +80 °C
- Weight = 0.023 kg/piece

- Adhesive magnet for tools

 Use under conveyor belts as tracking, for magnetizable conveying products or at higher conveying speeds

APPLICATIONS

- Fitting for all profiles of profile series 30
- Snap or slip the cover profile into profile groove
- Insert magnet into t-slot
- For fastening: (mighty recommended) Use end cap AL, set screw with square nut or t-slot bar

STORAGE BOXES

Type 1 Type 2





- Provision of small parts, screws, nuts etc. at assembly workstations
- Ergonomic workplace systems

ASSEMBLY

Mount storage boxes with storage box holder, 1-fold part no. 32.0509/0 or with multiple storage box holder part no. 32.0532/0 on tool holder plate or carrier

| Туре | Part no. | Measure A | Measure B | Dimension C | Color |
|------|-----------|-----------|-----------|-------------|-----------|
| 1 | 32.0540/0 | 360 | 210 | 147 | blue |
| | 32.0540/5 | 350 | 200 | 145 | black ESD |
| 1 | 32.0541/0 | 229 | 148 | 122 | blue |
| 1 | 32.0541/5 | 235 | 145 | 125 | black ESD |
| 1 | 32.0542/0 | 167 | 104 | 76 | blue |
| 1 | 32.0542/5 | 175 | 100 | 75 | black ESD |
| 2 | 32.0543/0 | 85 | 100 | 50 | blue |
| | 32.0543/5 | 95 | 100 | 50 | black ESD |


- TECHNICAL DATA
- Optimal overview and convenient access to the content
- Large handles on the front and back for easy handling
- Dimensionally stable
- Resistant to most acids and oils
- temperature resistance (-20° to +80°C)



STORAGE BOX SHELF Part no. 32.0514/0 2 **TECHN. DATA / ITEMS SUPPLIED APPLICATIONS** ASSEMBLY - Steel, powder-coated, grey - For semi open front containers and small - Fasten to the portal structure hardware - Freestanding or in combination with box - 3 levels

- Weight = 3.800 kg/piece
- For max. 12 semi open front containers, L= 165 mm, W= 105 mm, H= 75 mm
- holder part no. 32.0516/0 swiveling
- Optional: in ESD-design part no. 32.0514/6

STORAGE BOX HOLDER



- Steel, powder-coated, grey
- Fastening material
- Front handle bar
- With double articulated arm 700 mm long
- Load capacity 150 N
- Weight = 4.300 kg/piece



APPLICATIONS

- As storage area for semi open front containers and semi open front container racks

Part no.

32.0516/0



- Installation on the vertical strut of the portal structure
- Optional: in ESD-design part no. 32.0516/6

KANTAINER

The newly developed KanTainer offers the ideal prerequisite for implementing the principles of lean production in your company using Kanban control.



In combination with the mounting solutions and the ergonomic designed working places of MiniTec, a complete, safe and economic all-round-package for your manual production is ensured. The Kantainer is designed for maximum space utilization in the warehouse with optimal material provision at the workplace. The Kantainer offers all the prerequisites to make

FUNCTIONS

- For continuous kanban system: no transfer no error-prone refilling
- Total storage rack use by retractable grip plate
- Ergonomically optimized grip plate eases the removal
- Transparent cover against soiling and mixing of parts
- Cover as protection against unintentional opening or loss of parts
- Simple content control
- Transparent dosing disc: easy recognition of residual quantities
- Dosing disc prevents uncontrolled trickling out of small parts
- Secure stacking through locating pins and eyelets
- Double-sided labelling
- Retaining device at the back of the container
- Bottom guide rails for longitudinal and transverse transport

storage, order picking and assembly easier and safer. Thanks to the compatible system components of our extensive MiniTec modular system, we are able to optimally solve virtually every task in manual assembly.

TECHNICAL DATA


- Dimensions: 175x126x88 [mm]
- Superimposed load 50 kg
- Content load: 5 kg

- Temperature resistance: -20°C to +90°C
- Material: polypropylene, polystyrene
 - Color: Basalt grey (RAL 7012) [Part no.: 32.0870/0] Orange (RAL 2004) [Part no.: 32.0870/1] Black ESD conductive [Part no.: 32.0870/5]

The ESD-conductive Kantainer is the optimal and logical addition to our ESD workstation systems.



KANTAINER-SWIVEL CANTILEVER, 3-FOLD






APPLICATIONS

TECHN. DATA / ITEMS SUPPLIED

- Profile 45 x 32 F and 45 x 45 F
- heavy duty joint and swivel joint with clamping lever with supplied hardware
- Load capacity: max.= 100 N
- Weight = 1.916 kg/piece


- Accepting 3 KanTainers



ASSEMBLY

- Mount the heavy load hinge on the table

KANTAINER - SHELF (STRAIGHT)



TECHN. DATA / ITEMS SUPPLIED

- Side panels steel, powder coated, grey
- Intermediate struts of profile 23 x 30
- Delivery as construction set
- Fastening kit
- Weight = 3.400 kg/piece



APPLICATIONS

- Accepting 9 KanTainers
- Adjustable inclination
- With the hooks on the back, the shelf can also be hung in our profile grooves

Part no.

32.0876/0



ASSEMBLY

 Screw profiles to side panels with supplied mounting angles and mounting hardware

MONITOR SUPPORT LX AND LX HD



APPLICATION


The LX and LX HD monitor supports are suitable for a wide range of applications: suitable for large monitors, medium-sized televisions and all-in-one computers weighing up to 13.6 kg. The LX offers a large range of motion and is suitable for both sedentary and standing users, allows vertical adjustment of up to 51 cm and lateral adjustment of 157 cm.


ADVANTAGES

- More freedom and flexibility through maximum ergonomic comfort
- Maximum comfort when positioning the monitor
- Integrated cable management
- Up to 51 cm stepless height adjustment, meets the ergonomic principles of more than 90% of all users
- Arm can be pulled back over the base plate and fold up; suitable for storage in shelves or cupboards in confined spaces
- Outstanding viewing comfort prevents health risks in the neck and back
- LCD range up to 88 cm. Simply slide the screen to the side if you are not using it

| Part No. | LX HD arm for wall mounting 32.0623/0 | LX arm for wall mounting 32.0622/0 | |
|-----------------------|---|--|--|
| Scope of delivery | LX HD sit-stand-arm, extension, wall mounting base, VESA brackets incl. mounting material | LX LCD-arm, bracket arms, wall bracket base.Direct mounting on solid vertical surfaces incl. mounting material | |
| Maximum screen size | 46" | 24" | |
| | Screen size may vary. Details refer to the screen diagona | al | |
| Load-bearing capacity | 6,3–13,6 kg | 3.2-9.1 kg monitor depth can be greater than 5 cm reduce capacity | |
| Height adjustment | 51 cm | 33 cm | |
| Tilt function | 80° 75° / 5° | 75° 70° / 5° | |
| Swivel function | 360° | 360° | |
| Rotation | 90° Rotation with portrait / landscape mode | 90° Rotation with portrait / landscape mode | |
| VESA | 75x75mm/100x100mm/200x100mm/200x200mm | 75x75mm/100x100mm | |
| Depth | Foldable to 12 cm | Foldable to 13.4 cm | |
| Reach up | 84 cm | 64 cm | |
| Transport weight | 9,1 kg | 3,2 kg | |
| Transport dimensions | 64 x 38 x 19 cm | 53 x 29 x 19 cm | |
| | ACCESSORIES | | |
| 32.0612/0 | Keyboa | ard tray | |
| | Keyboard shelf made of sheet steel, powder-coated matt black for mounting on monitor carrier LX / LX HD. Rear cable entry for mouse and keyboard. The distance to the monitor is adjustable. For fastening the existing VESA holes are used. When used, the arm is additionally loaded with 2.4kg. | | |
| 32.0624/0 | Monitor handle Kit | | |
| P | Can be attached to many mounts using a bolt circle of 50 x 50mm, 100 x 100mm or 200 x 100mm. Robust design ensures long service life. Suitable for displays up to a size of 32 inches. When used, the arm is additionally loaded with 1.3 kg. | | |
| 39.0118/0 | Dual monitor support for LX HD | | |
| | Recording for 2 monitors and a handle - Integrated cable management - Load capacity: 6.3 - 10.5 kg - Height adjustment: 510 mm - Extension: up to 840 mm - Tilt function: 80° - Rotation: 90° - VESA mounting standard: 75 x 75 mm 100 x 100 mm - Maximum display size: 46 " - When used the arm is additionally loaded with 2.7 kg. | | |

STORAGE CONSOLE WITH CLAMPING LEVER






- Shelf for cabinet, chipboard, light grey
- Front edge 13 mm raised edges
- ESD on request
- Please state table width B2 and depth T3
- Load capacity: 400 N



APPLICATIONS

Continuously inclinable from -30° to +30°
 Rack is adjustable



32.0501/0

ASSEMBLY


- Fastening with 2 swivel plates to the portal structure
- without clamp lever **part no. 32.0501/1**

STORAGE SHELF / MONITOR SUPPORT ROTATING CRT

Part no.

Part no.

32.0512/0



TECHN. DATA / ITEMS SUPPLIED

- Steel, powder coated, light grey
- Double joint design, length 430 mm
- Monitor and keyboard panel rotatable
- Monitor panel: 370 x 370 mm
- Load capacity 150 N
- Weight = 4.200 kg/piece



APPLICATIONS

Provision of IT data, guidelines, Internet connection




- Screw onto the portal structure

- Optional as ESD version Part no. 32.0512/6

32.0517/0

MONITOR SUPPORT WITH KEYBOARD TRAY TFT



TECHN. DATA / ITEMS SUPPLIED

- Steel, powder-coated, grey
- Monitor and keyboard carrier with mouse rack
- With double-articulated swing boom
- Delivery as construction set
- ESD on request
- Load capacity 150 N
- Weight = 7.400 kg/piece



APPLICATIONS

- The mouse rack is shiftable and therefore suitable for right and left-handers




Part no.

OTHER VERSIONS

- Support with keyboard shelf with VESA connection adapter 75 mm part no. 32.0517/0
- Support with keyboard shelf with VESA connection adapter 100 mm part no. 32.0517/1
- Support without keyboard shelf with VESA connection adapter 75 mm part no.
 32.0525/0
- Support without keyboard shelf with VESA connection adapter 100 mm part no.
 32.0526/0

KEYBOARD STORAGE



TECHN. DATA / ITEMS SUPPLIED

- Stainless steel
- Stainless steel 2mm, grounded
- Rustproof
- For standard keyboards
- With slide nuts M6Z, ESD-compatible
- Fastening material
- Load capacity 150 N
- Weight = 2.477 kg/piece



APPLICATIONS

- For setting the keyboard on the workplace



Part no.




32.0518/0

ASSEMBLY

- Fasten to profile groove with supplied hardware

MONITOR CARRIER V 100



- Fastening kit
- Load capacity 150 N
- Weight = 0.568 kg/piece

- Monitor can be rotated through 180° - For VESA standard 75 x 75 mm / 100 x 100 mm


32.0053/0


ASSEMBLY

- Fasten to profile groove with supplied hardware.

32.0610/0

DOCUMENT BAR





APPLICATIONS

- Safe attachment of large drawings, instructions, plans
- Simply slip-in papers from below
- Attach to portal construction by screwing or gluing with double-faced adhesive tape



Part no.

ASSEMBLY

- Use the screws of fastening kit or fasten with adhesive tape on the back


Aluminium anodized

- With clamping balls made of special glass

TECHN. DATA / ITEMS SUPPLIED

- Length: 505 mm
- Other dimensions upon request
- Weight = 0.300 kg/piece

DOCUMENT SUPPORT



TECHN. DATA / ITEMS SUPPLIED

- Steel bracket, powder coated light grey
- 10 DIN A4 boards, transparent
- Border per 5 in blue and red
- 5 Slip-on tabs
- Weight = 1.240 kg/piece



APPLICATIONS

- Provision of job instructions, maintenance notes
- Control boards, general information
- Screw tight onto portal conscruction


Part no.

32.0605/0




Fastening with 2 hex socket cap screws M 06 x 16, 2 square nut M6 into profile groove

- ESD-design part no. 32.0605/6



TOOL SLIDER H



TECHN. DATA / ITEMS SUPPLIED

- ABS, Injection Mould, grey
- load capacity up to 600 N
- Weight = 0.010 kg/piece




APPLICATIONS

- Grab-supportive tool suspensions
- Suitable for all 45er profiles


Part no.

22.1213/0




ASSEMBLY

- insert both halves in profile groove and press together
- Optional: spring clip 60x6 part no.
 21.1699/0




C-SECTION RAIL 30



TECHN. DATA / ITEMS SUPPLIED

- Steel, galvanized
- $-I_x = 2.42 \text{ cm}^4$
- $-I_v = 1.45 \text{ cm}^4$
- ESD-compatible
- Weight = 1.560 kg/m
- Bar length = 6 m



APPLICATIONS

 Reception and guide of cable trolleys
 Reception and guide of tool trolleys to provide heavy tools Part no.


32.0220/0



ASSEMBLY

 Attach to portal structure with rail holder part no. 32.0222/0

RAIL HOLDER



TECHN. DATA / ITEMS SUPPLIED

- Steel, galvanized
- Square nut Z, ESD capable
- Weight = 0.250 kg/piece



APPLICATIONS

- Fastening the C-section rail onto the portal structure
- Fixation for C-rail 30 part no. 32.0220/0




32.0222/0

ASSEMBLY

- Fasten to the portal construction with supplied hardware

CLOSURE CAP FOR C-RAIL



TECHN. DATA / ITEMS SUPPLIED

- Plastic, black
- Weight = 0.006 kg/piece



- Closing of both rail ends

Part no.

Part no.

32.0223/0




ASSEMBLY

- Press onto C-profile rail

412 MINITEC PROFILE SYSTEM

<text>

TOOL TROLLEY



TECHN. DATA / ITEMS SUPPLIED

- Steel, galvanized
- 4 rollers, zinc plated, ball bearings sealed on both sides
- ESD-compatible
- Load capacity: 16 kg
- Weight = 0.210 kg/piece



APPLICATIONS

- Suspension of tools in the work area

Part no.

32.0224/0



ASSEMBLY

Push into C-section rail, secure ends with limit stop

CABLE TROLLEYS FOR ROUND CABLES

Part no.

Part no.


32.0225/0



- Suspension of hoses and pipes

- Supporting body: plastic, yellow
- 4 plastic rollers
- Load capacity: 8 kg
- Weight = 0.135 kg/piece

SWIVEL CANTILEVER C-RAIL 30



TECHN. DATA / ITEMS SUPPLIED

- Steel, powder-coated, grey
- $-\,180^\circ$ swiveling
- Fastening material
- Length: 692 mm
- Load capacity: 200 N
- Weight = 2.310 kg/piece



APPLICATIONS

- For compressed air and power tools




32.0230/0

- Slight slope to the rear, so that unused tool slides automatically from work area
- Fasten to the portal construction with supplied hardware
- Optional:as ESD design part no. 32.0230/6


SWIVEL ARM ECO 32.0201/0 Part no. TECHN. DATA / ITEMS SUPPLIED APPLICATIONS ASSEMBLY – Aluminium - For compressed air and power tools - Fixing to portal with angle - Fasten to the portal construction with - 200° swiveling supplied hardware - Fastening material – plain bearing – Length: 600 mm - Load capacity: max.= 100 N

– Weight = 1.100 kg/piece



TECHN. DATA / ITEMS SUPPLIED


- Steel, galvanized
- Without fastening kit
- Weight = 0.268 kg/piece



APPLICATIONS


 as depositing rack for semi-open front containers and storage containers Part no.

32.0306/0



ASSEMBLY

- simply hooked into handle profile 32 from both sides
- Recommended: If required, secure laterally against sliding of snap bolt 25 part no. 21.1758/0




– Weight = 0.078 kg/piece

APPLICATIONS

- Holder for various tools with ø 16 - 25 mm

Part no.






ASSEMBLY

 Fasten into the profile groove with supplied hardware and tighten the fastening screw

15.2 (c)

ATTACHMENT CLIP 16




TECHN. DATA / ITEMS SUPPLIED

- Steel
- Stainless steel 1.4319
- Attachment clip with fastening kit
- Square nut Z, ESD capable
- Weight = 0.028 kg/piece

416 MINITEC PROFILE SYSTEM

ATTACHMENT CLIP 8 32.0537/0 Part no. 1270 1341 2 M5 TECHN. DATA / ITEMS SUPPLIED **APPLICATIONS** ASSEMBLY – Steel - Holder for various tools with ø 8 - 12 mm - Fasten into the profile groove with supplied hardware and tighten the fastening screw - Stainless steel 1.4319

- Attachment clip with fastening kit
- Square nut Z, ESD capable
- Weight = 0.017 kg/piece



APPLICATIONS

- Tool holder for storage of tools, pins, etc. – Adjustable angle


Part no.

32.0536/0



ASSEMBLY

- Attach with fastening kit from items supplied to profile strut




TECHN. DATA / ITEMS SUPPLIED

- Stainless steel
- Material V2A, polished
- Fastening kit
- Square nut Z, ESD capable
- Weight = 0.402 kg/piece



STEEL BRACKET 250




TECHN. DATA / ITEMS SUPPLIED


- Steel, powder-coated, grey
- With welded-on clamps for setting on a 19 mm chipboard, for example
- Clamped using pretensioning and can be secured additionally with wood screws
- Weight = 0.214 kg/piece




As separating web for cartonsMagazine for flat parts



- Pull apart gently, stick on at the correct posi-
- tion and secure with suitable screw



DRAWING HOLDER



TECHN. DATA / ITEMS SUPPLIED

- Steel light grey, powder coated
- With double-articulated swing boom
- For DIN A4 format
- Load capacity 150 N
- Delivery as construction set
- ESD on request
- Weight = 4.000 kg/piece



APPLICATIONS


- For documents, control charts and drawings

Part no.


32.0608/0



- Fasten to the portal structure




QUICK LABEL 27 X 75



TECHN. DATA / ITEMS SUPPLIED

- Front, transparent
- Back, self-adhesive
- Open at the sides and on top
- Weight = 0.003 kg/piece




- Storage compartment identification
- Error-free scanning of barcodes
- For profile width 32

Part no.






- Attach with self-adhesive back
- Push in carton insert
- Cardboard insert not included in delivery scope, bows 20 pieces part no. 32.0601/1 please order separately



SEMI-OPEN COMPARTMENT BASE ELEMENT



TECHN. DATA / ITEMS SUPPLIED

- Steel light grey, powder coated
- With fastening bores Ø 9, spacing 160 mm
- Optical edge 45 mm for optimum overview
- Filling capacity =15 mm, sufficient for approx.120 sheets of paper
- With grey closing plate
- clear semi-open compartment (front plate)
- Weight = 0.634 kg/piece




APPLICATIONS

- For size DIN A4 documents

Part no.






ASSEMBLY

- Fasten to the portal structure
- Any time expandable with **part no. 32.0616/0**
- Extract the front panel during extension and attach it to the last extension element again

SEMI-OPEN COMPARTMENT EXTENSION ELEMENT





Part no.

APPLICATIONS

- For size DIN A4 documents
- Place base element on compartment part no. 32.0615/0

ASSEMBLY


- Filling capacity =15 mm, sufficient for approx.

- Steel, powder coated, light grey

TECHN. DATA / ITEMS SUPPLIED


- 120 sheets of paper
- Weight = 0.392 kg/piece





TECHN. DATA / ITEMS SUPPLIED

- Steel, powder coated, light grey
- With fastening bores Ø 4 mm, spacing approx. 16 mm
- With grey closing plate
- Weight = 0.500 kg/piece



- For size DIN A4 documents
- Optional:compartment single element DIN A4 portrait format with transparent locking plate part no. 32.0619/0

Part no.



32.0616/0




ASSEMBLY

- Attach to the portal structure or use as an extension element for the base element

32.0618/0

ADDITIONAL ANGLE FOR VIEWING COMPARTMENT





APPLICATIONS


- Fasten to the portal structure

TECHN. DATA / ITEMS SUPPLIED

- Steel light grey, powder coated
- With magnet strips
- Weight = 0.123 kg/piece
- For additional stabilisation on the bottom edge of the semi-open compartments

Part no.

CUP HOLDER



TECHN. DATA / ITEMS SUPPLIED

- PA, grey
- Cup with MiniTec company logo
- Fastening kit
- Weight = 0.388 kg/piece




APPLICATIONS

Cup or bottle holder for workplace systemsWith cut-out for cup handle

Part no.

32.0547/0




ASSEMBLY

- Fasten rectangular connectors to post profile with supplied hardware at a distance of 35 mm
- Insert cup holder in t-slot
- For adjustment use set screw M5


BOTTLES/DRINK CARTON HOLDER

Part no.

32.0507/0



WASTE SEPARATION



TECHN. DATA / ITEMS SUPPLIED

- Sturdy frame of profile 30 x 30, anodized E6
 / EV1
- Delivery as construction set
- With shelf
- 3 covers ABS, grey
- Weight = 7.023 kg/piece



- For separate collection of 3 kinds of recyclable materials
- Just put plastic bags over the screw heads
- Also suitable for outdoor deployment

Part no.






ASSEMBLY

- According to enclosed installation instructions

RECYCLABLE MATERIAL COLLECTOR FOR ATTACH-MENT

Part no.

32.0024/0





TECHN. DATA / ITEMS SUPPLIED

- Frame made of profile 30 x 30, anodized E6
 / EV1
- 2 covers ABS, grey
- 2 mounting angles 25
- Weight = 1.915 kg/piece



APPLICATIONS


- For separate collection of 2 kinds of recyclable materials
- Just put plastic bags over the screw heads



ASSEMBLY


- Attach to profile frame with fastening materials included

TOOL CASE S AS SET



TECHN. DATA / ITEMS SUPPLIED


- Tool quiver, rubber, black
- Swivel bracket, steel, grey, powder-coated
- With fastening material steel, zinc plated
- Weight = 0.830 kg/piece



APPLICATIONS


For secure storage of drills, battery-operated screwdrivers and other tools

- Adjustable angle




ASSEMBLY

 Fasten to the profile brace with supplied hardware




TOOL CASE S



TECHN. DATA / ITEMS SUPPLIED

– Rubber, black

– Weight = 0.492 kg/piece



For secure storage of drills, battery-operated screwdrivers and other tools

Part no.





- Drill 2 bores ø 7 mm, distance of 45 into profile
- Fasten with screws M8 x 16

26.3002/0

ADAPTER FOR TOOL CASE



APPLICATIONS

- POM, white
- Standard: without machining
 Optional: with machining eg. aptly drilled or
 milled for special tools

TECHN. DATA / ITEMS SUPPLIED


- Weight = 0.225 kg/piece
- Adapter for rod screwdrivers, special screwdrivers, pneumatic screwdrivers and smaller hand tools

ASSEMBLY

- Press into tool quiver

Part no.

SWIVEL HOLDER



TECHN. DATA / ITEMS SUPPLIED

- Steel, powder-coated, grey
- Powder coated RAL 7012
- Weight = 0.283 kg/piece



APPLICATIONS


 For swiveling attachment of toolboxes, profiles or shelves Part no.

26.3001/2




ASSEMBLY

 With screws M8 x 16 or clamping lever and M8 sliding nut




BRUSH STRIP 30



TECHN. DATA / ITEMS SUPPLIED

- PVC strip with brush
- Manufacturing length: 1000 mm
- Weight = 0.128 kg/m




AFFLICATI

- Sealing of doors, lids
- Static strap cleaning in case of minor soiling
- Guiding and carrying in conveyor technology


Part no.

22.1150/0




ASSEMBLY

- Insert or clip into profile groove



HORIZONTAL DOUBLE OUTLET



TECHN. DATA / ITEMS SUPPLIED

- Schuko 10 / 16 A 250 V
- IP 44 shatter-proof
- Housing 75 x 75 x 58 mm
- Fastening material
- With adapter plate and screws
- Weight = 0.389 kg/piece




APPLICATIONS

- For power supply at the workplace


Part no.

32.0774/0




ASSEMBLY

Attach the adapter plate to the profileFasten double outlet to the adapter plate



TOGGLE SWITCH/POWER OUTLET



TECHN. DATA / ITEMS SUPPLIED

- OFF switch, 10A x 250V
- Schuko 10 / 16 A 250 V, IP 44 shatter-proofed
- Housing 75 x 75 x 58 mm
- Fastening material
- With adapter plate

- Weight = 0.389 kg/piece




APPLICATIONS


- For switching lights on and off



- Attach the adapter plate to the profile
- Fasten the switch on the adapter plate



SOCKET STRIPS 7-FOLD



TECHN. DATA / ITEMS SUPPLIED

- 7-fold with additional switch
- Rocker switch, illuminated
- Cable length 2 m
- Max. 3500W / 16A / 230V
- Weight = 0.858 kg/piece



APPLICATIONS

Oblique socket arrangement


Part no.

32.0703/0




ASSEMBLY

 Fasten to profile groove with supplied hardware



SOCKET STRIP ALU 6-FOLD



TECHN. DATA / ITEMS SUPPLIED

- Housing Aluminum natural anodized
- Rocker switch, illuminated
- Max. 3500W / 16A / 230V
- Cable length 2 m
- Weight = 0.848 kg/piece



- Oblique socket arrangement

Part no.

32.0705/0



ABBEIT

 Fasten with fastening material to profile groove

