FORM NR ROTARY INDEXING RINGS [ED. 01].		
Company	Send to:	
Email	comercial@fluidotronica.com For more information: +351 256 681 957 www.fluidotronica.com	
Phone		
· · · · · · · · · · · · · · · · · · ·	t the right product for you. Please note that we can only guarantee If important information is missing, we will contact you. You can	
Model	Motor Mounted	
□ NR 750Z □ NR 1500Z	on the bottom 90° inside	
□ NR 1100Z □ NR 2200Z	90° outside	
Indexing time	Additional components (optional)	
[Based on the calculated mass moment of inertia, do you require]	Raised support for fixed stationary plate: H [mm]	
The shortest indexing time		
A longer indexing time of approx. [seg.]	Raised support for rotary ring: H [mm]	
Angle of rotation [9]		
Standing time [seg.]	Base frame [Please refer to indexing machine bases]	
Colour of the rotary indexing ring RAL 7035 [light grey-standard] Special colour RAL [education	extra charge]tted]	
REQUIRED TO SPECIFY YOUR NR TABLE		
The following specification regarding your configuration is fur		
Indexing ring	Fixture and parts	
Outer diameter [mm]		
Inner diameter [mm]		
Thickness [mm]	3 ,	
Material AlMg4.5Mn Other		
Please draw a sketch of how your load is build on the table.		
Total mass moment of inertia (additional indexing plate and add-ons	(s) [kg m²]	
Additional industry what		
Additional indexing plate Included in the scape of offer and delivery. Proceedings of the scape of offer and delivery.	sessing according to drawing No.	
Included in the scope of offer and delivery Proc	cessing according to drawing No	
Electrical data		
☐ WEISS control package [Cables length [5, 10, 15, 20 ou 25 m]	
Servo motor, amplifier, W.A.S. Software	Hand-held terminal (optional)	

FORM NR ROTARY INDEXING RINGS [ED. 01].

PAG 2/2

Send to: comercial@fluidotronica.com For more information: +351 256 681 957 www.fluidotronica.com



Please fill out the following questionnaire carefully so we can select the right product for you. Please note that we can only guarantee the best choice for you if all information is completely available. If important information is missing, we will contact you. You can complement this information with photographs, 3D files, etc.

\square Supply of customers n	notor and controller***
Customer to fit m	notor***
Manufacturer	
Туре	
*** Please forward a drawin	g of motor flange
[Motor specification following co	nsulting Fluidotronica]
Interface to the customer	PLC
☐ Digital I/O	PROFINET (W.A.S. 2 only)
Profibus-DP	EtherCAT (W.A.S. 2 only)
EtherNet / IP (Rockwel	1)
Interface to W.A.S. – WEISS	S Application Software
RS232 and Ethernet are incl	uded in the scope of delivery
Converter USB to RS23	32