

Company _____

Email _____

Phone _____

Send to:
 comercial@fluidotronica.com
 For more information:
 +351 256 681 957
 www.fluidotronica.com



Please fill out the following questionnaire carefully so we can select the right product for you. Please note that we can only guarantee the best choice for you if all information is completely available. If important information is missing, we will contact you. You can complement this information with photographs, 3D files, etc.

Model

- TO 150C (A/B) TO 750C TO 220C (A/B)

The configuration (A/B) is selected by us on the basis of your indexing time specifications.

Connection plug arrangement (TO 150C / TO 220C)

- parallel lateral



Indexing time

[Based on the calculated mass moment of inertia, do you require]

- The shortest indexing time
- A longer indexing time of approx. [sec.] _____
- Angle of rotation [°] _____
- Standing time [sec.] _____
- Mass moment of inertia (additional indexing plate and add-ons) [kg m²] _____

Direction of connection (TO 750C)

- below
- left
- right



Colour of the indexing table (TO 750C only)

- RAL 7035 [light grey] Special colour RAL [extra charge] _____

Indexing ring

Diameter [I/D mm] _____

Thickness [mm] _____

Material Al St other _____

Fixtures and parts

Number _____

Weight per station [kg] _____

Diameter of the center of gravity [mm] _____

Dial plate

- Included in the scope of offer and delivery Processing according to drawing No. _____

Electrical data

- WEISS control package
 Servo motor, amplifier, W.A.S. Software
- Cables length [5, 10, 15, 20 or 25 m] _____
- Hand-held terminal (optional)

Electrical source

- TO 150C 1 oder 3 x 208 ... 230 V ~ 50/60 Hz
- 3x400 ... 480 V ~ 50/60 Hz
- TO 220C 1 oder 3 x 208 ... 230 V ~ 50/60 Hz
- 3x400 ... 480 V ~ 50/60 Hz
- TO 750C 3x400 ... 480 V ~ 50/60 Hz

Send to:
comercial@fluidotronica.com
For more information:
+351 256 681 957
www.fluidotronica.com



Please fill out the following questionnaire carefully so we can select the right product for you. Please note that we can only guarantee the best choice for you if all information is completely available. If important information is missing, we will contact you. You can complement this information with photographs, 3D files, etc.

Interface to the customer PLC

- Digital I/O
- PROFINET (W.A.S. 2 only)
- Profibus-DP
- EtherCAT (W.A.S. 2 only)
- EtherNet / IP (Rockwell)

Interface to W.A.S. – WEISS Application Software

RS232 and Ethernet are included in the scope of delivery

- Converter USB to RS232

Encoder

TO 150C / TO 220C

- ECN 113 ± 25"
- ECN 225 ± 15"

TO 750C

- Incremental
- Absolute BISS
- Absolute DriveCliq