FORM SH HANDLING SYSTEM [ED. 01].				
Company Email Phone			Send to: comercial@fluidotronica.com For more information: +351 256 681 957 www.fluidotronica.com	
th	ease fill out the following questionnaire carefully so we can select to be best choice for you if all information is completely available. If the perplement this information with photographs, 3D files, etc.	- ,	,	
	Mass moment of inertia [kgm²] Weight (gripper + workpiece) [kg]	<b>Accesso</b> Cla	ories mping set	
Elec	ctrical components	Supply	voltage	
	WEISS control package	1 x 208 a 230 V ~ 50/60 Hz *		
	Amplifier, W.A.S Software	☐ 3 x	<ul> <li>3 x 208 a 230 V ~ 50/60 Hz</li> <li>3 x 400 a 480 V ~ 50/60 Hz (larger installation dimensions)</li> </ul>	
	Cable lengths [5, 10, 15, 20 ou 25 m]			
	Interface to customer PLC	(larg		
	☐ Profibus-DP			
	☐ Digital I/O			
	PROFINET (W.A.S. 2 only)			
	EtherCAT (W.A.S. 2 only)			
	Ethernet/IP (Rockwell)			
	Interface to the WEISS Application Software (W.A.S.)			
	RS232 and Ethernet included as standard			
	USB-to-RS232 adapter			

Cycle time calculation – please give us an idea of your desired motion sequence

